


**■ Description**

IPS021 is the Noise-improved version of IPS020PE Differential output SPXO-IC series. Output type is LVPECL.

**■ Features**

- Operation temperature : -40°C~125°C
- Power supply voltage : 2.375V~3.63V
- Standby function : Oscillation stop
- Output : LVPECL
- Crystal mode : Fundamental & 3rd overtone
- Small chip size : 0.65mm × 0.75mm
- Pad layout : Straight type & Flip type
- Duty cycle : Within 50%±5%
- Low Phase Jitter : ~40fs@F0=156MHz,Vdd=3.3V

**1. Part number rule**


## 2. Series

Part Number	Output	Crystal Frequency f (MHz)			Divide	Output Frequency F0 (MHz)		Remarks
		Mode	Min.	Max.		Min.	Max.	
IPS021 4 M 0 P S	LVPECL	Fund.	50	125	1/1	50	125	
IPS021 4 M 0 P F								
IPS021 5 M 0 P S			100	160				
IPS021 5 M 0 P F								
IPS021 4 M T P S		3rd	100	125		100	125	
IPS021 4 M T P F								
IPS021 5 M T P S			125	160		125	160	
IPS021 5 M T P F								

## 3. Absolute Maximum Ratings

 $V_{SS}=0V, T_a=25^{\circ}C \pm 2^{\circ}C$ 

Parameter	Symbol	Condition	Ratings		
			Min	Max	Unit
Supply Voltage	$V_{DD}$		$V_{SS}-0.5$	5.0	V
Input Voltage	$V_{IN}$	All Input Pin	$V_{SS}-0.5$	$V_{DD}+0.5$	V
Output Voltage	$V_{OUT}$		$V_{SS}-0.5$	$V_{DD}+0.5$	V
Output Current	$I_{OUT}$			25	mA
Junction Temperature	$T_j$		-55	150	$^{\circ}C$
Storage Temperature	$T_{stg}$		-55	125	$^{\circ}C$

## 4. Recommended Operating Condition

 $V_{SS}=0V, T_a=-40^{\circ}C \sim 125^{\circ}C$ 

Parameter	Symbol	Condition	Min	Typ	Max	Unit	Note
Supply Voltage	$V_{DD}$		2.375		3.63	V	$V_{DD}$
“H” Input Voltage	$V_{IH}$		$V_{DD} \times 0.7$			V	CE
“L” Input Voltage	$V_{IL}$				$V_{DD} \times 0.3$	V	CE
Input Voltage	$V_{IN}$		$V_{SS}$		$V_{DD}$	V	CE
Output Load Resistance	RL	LVPECL *	49.5	50.0	50.5	$\Omega$	OUT
Ambient Temperature	$T_{opt}$		-40		125	$^{\circ}C$	

This IC has enough immunity against ESD and Latch-up, but handle with care.

\* Terminate to  $V_{DD}-2.0V$

**5. Electrical Specification**
**5-1 LVPECL Output**
**5-1-1 DC Characteristics**

 Unless otherwise stated,  $V_{DD}=2.375V\sim 3.63V$ ,  $V_{SS}=0V$ ,  $T_a=-40^{\circ}C\sim 125^{\circ}C$ 

Parameter	Symbol	Condition	Specification			Unit
			Min	Typ	Max	
Output leak current	$I_z$	CE=0.3V			10	$\mu A$
“L” input current	$I_{IL}$	$V_{IN}=V_{SS}$		-10		$\mu A$
“H” output voltage*	$V_{OH}$	CE=Open, OUT/OUTN	$V_{DD}$ -1.105	$V_{DD}$ -0.950	$V_{DD}$ -0.860	V
“L” output voltage*	$V_{OL}$		$V_{DD}$ -1.810	$V_{DD}$ -1.700	$V_{DD}$ -1.590	V
Current consumption*	$I_{DD}$	IPS0214M0P, F0=122MHz			55.0	mA
		IPS0215M0P, F0=160MHz			60.0	
		IPS0214MTP, F0=125MHz			55.0	
		IPS0215MTP, F0=160MHz			60.0	
Current consumption at oscillation stop	$I_{DDD}$	CE=GND			10	$\mu A$

 \*Condition :  $V_{DD}=3.3V$ , CE=Open,  $R_L=50\Omega$  (Terminated to  $V_{DD}-2.0V$ )

**5-1-2 Switching Characteristics**

 Unless otherwise stated,  $V_{DD}=2.375V\sim 3.63V$ ,  $V_{SS}=0V$ ,  $T_a=-40^{\circ}C\sim 125^{\circ}C$ 

Parameter	Symbol	Condition	Specification			Unit
			Min	Typ	Max	
Oscillation start up time	$T_{start}$	Fund			2.0	ms
		3rd			10.0	
Output Disable Time	$T_{plz}$				200	ns
Output Enable Time	$T_{pzl}$	Fund			2.0	ms
		3rd			10.0	
Rise time / Fall time	$T_r / T_f$	20%~80% $V_{opp}$			0.50	ns
Output Duty Ratio	Duty	1/2 $V_{opp}$ point	45		55	%
Output Swing	$V_{opp}$		0.4			V
Freq. $V_{DD}$ deviation	$F_{vst}$	$V_{DD}=2.5V \pm 5\%$			$\pm 2.0$	ppm
		$V_{DD}=3.3V \pm 10\%$			$\pm 2.0$	

 Condition :  $V_{DD}=3.3V$ , CE=Open,  $R_L=50\Omega$  (Terminated to  $V_{DD}-2.0V$ )





Fig. 5-1 Output Wave Form (Duty, Tr, Tf, V<sub>OH</sub>, V<sub>OL</sub>, V<sub>opp</sub>) of LVPEL



$V_{IH}$  : Threshold voltage for Oscillation Start  
 $V_{IL}$  : Threshold voltage for Oscillation Stop

Fig. 5-2 Input output signal timing

**6. Circuit Parameters of Oscillator (Reference Data for Circuit Design)**

Ta=25°C

Parameter		Symbol	Condition	Min	Typ	Max	Unit
Feedback Resistor	IPS0214M0P	Rf	Refer to Fig. 6-1		200		kΩ
	IPS0215M0P				2.25		
	IPS0214MTP				1.5		
Driving Resistor	IPS0214M0P	Rd			750		Ω
	IPS0215M0P				500		
	IPS0214MTP				50		
	IPS0215MTP				50		
Oscillation Capacitor	IPS0214M0P	Cg			5.0		pF
		Cd			8.0		
	IPS0215M0P	Cg			5.0		
		Cd			7.0		
	IPS0214MTP	Cg			7.0		
		Cd		14.0			
	IPS0215MTP	Cg		7.0			
		Cd		12.0			

\*The above values are the design values and are not guaranteed by test.






Fig. 6-1 Block Diagram

**7. Pad Layout**  
**7-1 Straight Type**


- Die Size: 0.65mm × 0.75mm
- Pad Size: 80um □
- Thickness: 150um ±20um
- IC Backside: Gnd or Open
- Swapping of OUT/OUTN with wire bond is acceptable

Pad Name	Function	Location (μm)	
		x	y
VDD	(+) Power Supply	-216	266
X1	Crystal Feedback	-216	83
X2	Crystal Drive	-216	-83
CE	Oscillation stop "L": High-Impedance	-216	-266
NC	NC	216	-266
VSS	(-) Ground	216	-83
OUTN	OUT(Complementary)	216	90
OUT	OUT(True)	216	266
Chip Center		0	0


□ \* LOGO

**7-2 Flip Type**


- Die Size: 0.65mm × 0.75mm
- Pad Size: 80um □
- Thickness: 150um ±20um
- IC Backside: Gnd or Open
- Swapping of OUT/OUTN with wire bond is acceptable

Pad Name	Function	Location (μm)	
		x	y
CE	Oscillation stop "L": High-Impedance	-216	266
X1	Crystal Feedback	-216	83
X2	Crystal Drive	-216	-83
VDD	(+) Power Supply	-216	-266
OUTN	OUT(Complementary)	216	-266
NC	NC	216	-83
OUT	OUT(True)	216	90
VSS	(-) Ground	216	266
Chip Center		0	0

□ \* LOGO




**IMPORTANT Notice for CE function**

- ※ Oscillation will not be activated when CE=Open after CE=Low if Rex is not large.
- ※ Reference value of Rex is over 10MΩ with CE=Open usage.
- ※ There is no such issue with CE=VDD usage.

Rex : Resistance value between CE and VSS of package

8. IC Part # Identification



Part #	Code 1~8	Code 9, 10
IPS0214M0Pq	■ □ □ □ □ □ □ □	□ □
IPS0215M0Pq	■ □ ■ □ □ □ □ □	□ □
IPS0214MTPq	■ □ □ ■ □ □ □ □	□ □
IPS0215MTPq	■ □ ■ ■ □ □ □ □	□ □

□ : Fuse no cut ■ : Fuse cut

**9. Revision History**

Revision No.	Revision Date	Revised items	Before Revision	After Revision
SD-7.2	2025/11/04	Wafer thickness 100um (Flip)	Listed	As requested
		IPS0214M0PF	Unlisted	Listed
		IPS0214MTPF	Unlisted	Listed
		IPS0214M0PS	Unlisted	Listed
		IPS0214MTPS	Unlisted	Under Development
		I <sub>DDD</sub> Condition	CE≤0.3V	CE=GND
SD-7.3	2026/06/01	IPS0214MTPS	Under Development	Listed